



Fast concrete removal for a rough finish

5 x 50mm (2") heads operating at 1300BPM delivers the ultimate demolition tool

FEATURES

- **Adjustable handle**
- **Vibration reduced**
- **Built in dead man's handle**
- **Large wheels** for rough terrain
- **Lifting eye** for ease to manoeuvre
- **Dust Free Working:** In-built vacuum port
- **Internal components** sealed against dust
- **Exhaust** away from operator for more efficient use of vacuum

APPLICATIONS

- Reducing high spots
- Texturing bridge decks for sealants
- Roughening surfaces to anti-slip floors
- Roughening surfaces for new overlays
- Breaking down hard coatings prior to floor blast cleaning, reducing cost of spent blast media

CONSUMABLES

Applications	Used with consumables:	Part No.
<ul style="list-style-type: none"> ✓ Levelling floors ✓ Reducing concrete ✓ Removal of floor paints & coatings 	 <p>Cruciform scabbler head</p>	441.5360
<ul style="list-style-type: none"> ✓ Laitance removal from large floor areas ✓ Roughing concrete prior to resurfacing ✓ Bridge deck preparation for 'waterproofing' 	 <p>5 point bush hammer scabbler head</p>	441.5359
<ul style="list-style-type: none"> ✓ Levelling uneven joints ✓ Creating excellent bond profile for epoxies, urethanes or thin overlays 	 <p>9 point bush hammer scabbler head</p>	441.5369

OPTIONAL ACCESSORIES

TVS™ - Trelawny Vacuum System

Where control of nuisance and hazardous dust is necessary Trelawny MHS5 can be used with:

- A45 electric dust collector
- Part No: 303.4110 (110V)**
- Part No: 303.4220 (220V)**



TECHNICAL DATA

Model	Part No.	Weight (kg)	Length (mm)	Height (mm)	Width (mm)	Cutting width (mm)	B.P.M (Blows per minute)	Air Consum. (litres per second – cubic feet per minute)	Noise Lpa SPL	Vibration (AEQ) m/s ²
MHS5 5 point head	159.5050	114	110 (43.3")	970 (38.18")	720 (28.34")	290 (11.4")	5 x 1300	38 lps (80 cfm)	94.7 dB(A)	16.5
MHS5 9 point head	159.5075	114	110 (43.3")	970 (38.18")	720 (28.34")	290 (11.4")	5 x 1300	38 lps (80 cfm)	94.7 dB(A)	16.5

D Designates tools & machines which can be used with Trelawny range of dust collectors for the containment of hazardous & nuisance dust