



Husqvarna K 760 Cut-n-Break

Our Cut-n-Break method is the natural choice when you need to cut deep at low maintenance costs. The K 760 Cut-n-Break enables you to cut as deep as 400 mm from one side. The two high-speed blades make a core in the saw cut, which can then easily be broken off using the accompanying breaking tool. This way you easily work your way through the material, at a very low diamond tool and maintenance cost. Delivered with twin blades and a breaking tool.



COST-EFFICIENT CUTTING METHOD

With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.



EXCEPTIONAL CUTTING DEPTH

The long body and double cutting blades allow you to make cuts up to 400 mm deep.



HIGH PERFORMING BLADES INCLUDED

Twin blades, with a very stable core and cutting performance are delivered with the machine.



OPTIMISED ENGINE PERFORMANCE

Optimised engine performance through efficient cylinder design, digital ignition system and X-Torc engine technology.

Features Husqvarna K 760 Cut-n-Break

- Easy to start
- Light and powerful
- The only time the filter needs to be checked and changed is if you experience lack of power.
- High power with less fuel
- Our X-Torq® engine produces less emissions, lower fuel consumption and produces more power.
- Blade retarder
- Our dust-sealed starter, where the return spring and the pulley bearing are sealed, gives a virtually maintenance free starter. Developed with a durable starter cord.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- The water adjustment gives an efficient dust management and makes operation easier and more efficient.
- Reduced vibrations in the cutter handle for more comfort and longer operation periods.
- EasyStart ensures easier starting by reducing the compression in the cylinder.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	73.5 cm ³ / 4.48 cu.inch
Power output	3.7 kW
Fuel tank volume	0.9 lit / 30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	1.9 m/s ²
Vibrations rear handle	2.8 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	230 mm / 9 inch
Max cutting depth	400 mm / 16 inch
Weight (excl. cutting equipment)	9.6 kg / 21.2 lbs
Weight incl. cutting equipment	11.1 kg / 24.5 lbs

