




Husqvarna FS 410 D

Our highly versatile FS 410 D is a compact diesel push floor saw developed with a clear focus on your comfort. Ideal for small to mid-sized service and repair jobs in asphalt and concrete. Cuts up to 189 mm deep.



LOW VIBRATIONS

Engine and blade shaft mounting system increases comfort and gives excellent cutting performance.



LOW MAINTENANCE

The IntelliSeal blade shaft system allows for a minimum of 250 maintenance-free hours without daily greasing of bearings.



EASY TO ADJUST THE BLADE

Spring-assisted screw feed facilitates blade adjustment in and out of the cut.



EASY TO TRANSPORT

Compact saw that is easy to lift.

Features Husqvarna FS 410 D

- Provides a closer and more comfortable position to the cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.

TECHNICAL SPECIFICATION	
Motor manufacturer	Yanmar
Motor spec	Diesel L100N
Max output (As rated by the engine manufacturer)	6.6 kW / 8.85 hp
Engine/motor RPM	pos1:3600 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	435 cm ³ / 26.55 cu.inch
Cylinder bore	86 mm / 3.39 inch
Cylinder stroke	75 mm / 2.95 inch
Fuel tank volume	5.4 lit / 1.43 gal.
Air filter type	Dry element
Starter	Recoil
Engine cooling	Air
Belt	Poly V
Oil capacity, l	1.6 lit
Diamond blade, max	500 mm / 20"
Max cutting depth	189 mm / 7.6 inch
Spindle diameter	25.4 mm / 1"
Blade depth control	Handwheel
Blade flange	114 mm / 4.5"
Blade shaft RPM	2600 rpm
Arbor size	25.4 mm / 1"
Axle front	25.4 mm / 1 inch
Rear axle diameter	25.4 mm / 1 inch
Handle bars	Adjustable in height
Primary wheel size	Outside diameter: 125 Wheel width: 40 Inner bore: 20 mm / Outside diameter: 4.92 Wheel width: 1.57 Inner bore: 0.79"
Secondary wheel size	Outside diameter: 203 Wheel width: 51 Inner bore: 25.4 mm / Outside diameter: 7.99 Wheel width: 2.01 Inner bore: 1"
Blade guard attachment	Slip-on
Blade guard type	Slip-on
Weight	145 kg / 319.66 lbs
Weight incl. packaging	196 kg / 432.1 lbs
Product size, LxWxH	1550x655x1200 mm / 61.02x25.79x47.24 inch
Sound power level, guaranteed (LWA)	108 dB(A)
Sound pressure	91 dB(A)
Hand arm vibration (Aeq)	4.4 m/s ²

