

**DESCRIPTION    SPECIFICATIONS    APPLICATIONS**

**Reference** 540680P

**DATA SHEET**

Height	96cm
Weight	80kg
Size WxL	60x110cm
Prep Rate	200m/hr
Vibration Level	2.5m/s
Noise Level	76dB

**INFO**

- SWM680P Power Sponge 4hp
- Petrol motor
- Uses either 620 or 680 sponges
- For cement & epoxy grouts
- Quickly cleans grout from quarry tiles
- Granite sets & paviors
- Leaves uniform & strong joint
- For external pavements & pedestrian areas
- Saves up to 70% of grouting time & labour

The SWM machines use a continuous sponge band that is fed through a water bucket and rollers; the excess sludge and water is squeezed out leaving the sponge clean to repeat the cycle

The schwammfx machines are for cleaning cements and grouts from quarry tiles, external paviors, natural stone and granite sets

The grout is pumped or poured into the joint; the schwammfx machine is used to pass over the newly grouted area and to sponge off the residue leaving a clean surface and compact joint

The system improves the joint quality, avoiding washing away the cement in the joint

The machines will mechanically do the time consuming "hands and knees" job of removing cementitious and epoxy grout

**SPECIFICATIONS**

- Petrol motor
- Weight 80kg
- Size WxL 60x110cm
- Height 96cm
- Sponge width 36cm
- Prep rate 200m/hr
- Vibration level 2.5m/s
- Noise level 76dB

**APPLICATIONS**

- Cleaning tiles of cement residues
- Spinging off grouts
- Finishing granite sets